

# CS-2030 Specifications

## BASIC SPECIFICATIONS:

Configuration:	Desktop Digital Copier with Standard 250 x 2 Paper Drawers Plus 50 Sheet Multi-Purpose Tray, Optional Network Printing, Scanning and Fax.
Resolution:	600 x 600 DPI Resolution / 256 Levels, Fast 1200 DPI Print Resolution
Copier Memory:	Standard 64MB RAM
Magnification:	Full Size, Reduction, Enlargement, Plus 50-200% Zoom
Electrical Requirements:	120V, 60Hz, 9A
Dimensions:	22"W x 24"D x 22"H
Weight:	102 lbs
Max Monthly Volume:	30,000 Pages Per Month

## OUTPUT SPEEDS:

Warm-Up Time:	Within 30 Seconds
First Copy Out:	5.5 Seconds
Pages Per Minute:	20 Letter, 11 Legal, 10 Ledger

## PAPER SUPPLY:

Standard Paper Sources:	Dual 250 Sheet Drawers, 50 Sheet MPT, Auto Selection / Switching
Drawer Paper Size:	5.5" x 8.5" - 11" x 17"
MPT Paper Size:	5.5" x 8.5" - 11" x 17"
Std / Max Paper Capacity:	550 / 1,050
Paper Weight:	17-21 lb Bond via Paper Drawers, 12 lb Bond - 88 lb Index via MPT
Input Materials:	Bond Paper, Recycled Paper, Transparencies, Labels, Envelopes

## COPY FUNCTIONS:

Imaging Modes:	Text, Photo, Text / Photo, Auto, Manual, ECO
Continuous Copy:	Up to 250, Auto Reset to 1
Additional Features:	Auto Magnification and Paper Select, Book Mode, Combine Image, Erase Mode, Image Rotate, Interrupt, Margin Shift, 100 Management Codes

## PAPER HANDLING OPTIONS:

### DOCUMENT PROCESSOR: SRDF-1

Type:	Reversing Automatic Document Processor
Acceptable Originals:	5.5" x 8.5" - 11" x 17", Mixed Size
Capacity:	70 Sheet RADF / 20 Letter Size Originals Per Minute
Paper Weight:	9- 42 lb Bond
Dimensions/Weight:	21.8"W x 18.8"D x 4.8"H / 23.1 lbs

### DOCUMENT PROCESSOR: STDF-3

Type:	Sheet Through Automatic Document Processor
Acceptable Originals:	5.5" x 8.5" - 11" x 17", Mixed Size
Capacity:	70 Sheet ADF / 20 Letter Size Originals Per Minute
Paper Weight:	9- 42 lb Bond
Dimensions/Weight:	21.8"W x 18.8"D x 4.8"H / 15.2 lbs

### DUPLEX UNIT/JOB SEPERATOR: AD-61

Paper Size:	5.5" x 8.5" - 11" x 17"
Paper Weight:	17-21 lb Bond
Duplex Modes:	Standard 1:2, 2:2, Book: 2, 2:1
Stack Capacity (Job Seperator):	100 Sheets

### DUPLEX UNIT FOR INTERNAL FINISHER: AD-62

Paper Size:	5.5" x 8.5" - 11" x 17"
Paper Weight:	17-21 lb Bond
Duplex Modes:	Standard 1:2, 2:2, Book: 2, 2:1

### INTERNAL FINISHER: F-2205

Stack Capacity:	500 Sheets
Paper Weight:	17 - 21 lb Bond
Staple Capacity:	30 Sheets: 8.5" x 11"; 20 Sheets: 8.5" x 14" - 11" x 17"
Edge Staple Position:	1 Position
Dimensions / Weight:	15.4 lbs

### PAPER DRAWER: ST-12

Paper Capacity:	250 Sheets
Paper Weight:	17 - 21 lb Bond
Paper Size:	5.5" x 8.5" - 11" x 17"
Dimensions / Weight:	21.6"W x 22.0"D x 4.5"H / 22 lbs

## CONNECTIVITY OPTIONS:

### PRINT: PRINT SYSTEM (K)

Controller:	Embedded PowerPC405 / 200 MHz Controller
Printer Memory:	Standard 8MB, Upgradeable to 136MB, Standard CF Card Slot (Type 1)
Supported PDL/Emulations:	PRESCRIBE, PCL6 (PCL XL, PCL 5e), KPDL2 (PS2)
Fonts:	80 Outline Fonts for PCL/KPDL, 1 Bitmap Font
Windows™ OS Compatibility:	Windows™ 95/98/Me/NT4.x/2000/XP
Novell™ OS Compatibility:	Novell NetWare™ 3.x/4.x/5.x
Mac OS Compatibility:	OS 8.x/9.x/10.x
UNIX OS Compatibility:	Sun OS 4.1.x; Solaris 2.x; AIX, HP-UX (LPR)
Connectivity / Interface:	Standard Parallel IEEE1284,
KUIO LV Expansion Slot (1):	Optional IB-21 10/100BaseTX, IB-20 10/100BaseTX; 10Base2; Optional IB-22 Enhanced Wireless NIC
Supported Protocols:	TCP/IP, IPX/SPX, AppleTalk, NetBEUI
Driver:	KX Driver for Windows™, PPD for Mac, PPD for Linux/UNIX
Utilities:	KM-NET Viewer, KM-NET Remote Operation Panel, Network Advanced Setup Utilities, PRESCRIBE Utilities

### SCANNING: Scan System (A)

Resolution:	200, 300, 400, 600 DPI
Scan Speed:	Up to 10 Sheets Per Minute
File Formats:	PDF, TIFF
Connectivity:	Standard NS-20 10/100BaseTX, 10Base2
Supported Protocols:	TCP/IP
Scanning Features:	Scan to PC/File, Scan to E-Mail, TWAIN
Driver:	TWAIN Driver
Utilities:	KM Scanner File Utility, Scanner Delivery Utility Network Advanced Setup Utilities

### FAX: Fax System (B)

Compatibility:	G3
Transmission Speed:	Approximately 3 Seconds per page
Modem Speed:	33.6 Kbps with Auto Fallback
Data Compression:	JBIG, MMR, MR, MH
Fax Memory:	Std 8MB /Max 16MB
Additional Features:	Duplex TX/RX, Confidential RX/TX, Polling, Broadcasting, 2 in 1 RX

## ADDITIONAL OPTIONS:

Job Separator (J-1302), 8MB Fax Memory Board (FM1-8MB), Stand



Specifications and design are subject to change without notice.  
For the latest on connectivity visit [www.kyoceramita.com](http://www.kyoceramita.com).  
All trademarks and registered trademarks are the property of their respective manufacturers.

Kyocera Mita America, Inc. Headquarters: 225 Sand Road, PO Box 40008, Fairfield, NJ 07004-0008, USA  
©2003 Kyocera Mita America, Inc.

Item Code# 87164139



[www.copystar.com](http://www.copystar.com)